

WEST Search History

DATE: Monday, March 28, 2005

<u>Hide?</u>	<u>Set Name</u>	<u>Query</u>	<u>Hit Count</u>
		<i>DB=USPT,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR</i>	
<input type="checkbox"/>	L11	L9 and pin	1
<input type="checkbox"/>	L10	L9 same pin	0
<input type="checkbox"/>	L9	(first near2 boot near2 device) same (second near2 boot near2 device)	17
<input type="checkbox"/>	L8	L7 with plug\$4	58
<input type="checkbox"/>	L7	boot\$4 with pin	2536
<input type="checkbox"/>	L6	l1 same pin	2
<input type="checkbox"/>	L5	l1 same (direct\$4 near3 connect\$4)	0
<input type="checkbox"/>	L4	L1 same input same output	6
<input type="checkbox"/>	L3	L1 same connect\$4	24
<input type="checkbox"/>	L2	L1 same plug\$4	4
<input type="checkbox"/>	L1	((switch\$4 or chang\$4 or alter\$4) near3 boot\$4 near3 device)	151

END OF SEARCH HISTORY

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L4: Entry 2 of 6

File: USPT

Jun 22, 2004

DOCUMENT-IDENTIFIER: US 6754818 B1

TITLE: Method and system for bootstrapping from a different boot image when computer system is turned on or reset

CLAIMS:

21. A system for booting from multiple boot image sources, comprising: a plurality of boot devices, each boot device containing a copy of a boot image; selecting means for selecting a different boot device among said plurality of boot devices each time the system is turned on or reset; loading means for loading the boot image from one of the boot devices selected by the selecting means into a system memory, wherein the loading means comprises a system basic input/output system (BIOS) program, wherein the selecting means comprises a selector switch coupled between a controller and said plurality of boot devices, wherein when a power switch of the system is actuated, the selector switch connects a different boot device to a port designated as a boot device port.

[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)